

Biolease Standard

Environmentally Friendly Concrete Mould Release Agent

Description

Biolease Standard is a blend of bio-degradable vegetable oils emulsified in water and is designed for use in general site operations and pre-cast yards. The oil forms a physical barrier between the form and the concrete with the surfactant working in conjunction with the alkalinity of the concrete to produce a high standard of finish.

Advantages

- VOC free and low odour.
- Non-flammable.
- Safe to use and environmentally friendly.
- Readily bio-degradable.
- Clean equipment with water.
- Non-staining, suitable for white or coloured concrete.
- Easy to apply by spray or brush.
- Not easily washed off by rain.
- Forms may be stripped early when concrete permits.
- Suitable for the application of other coatings, sealers and mortars.

Technical Information

| | |
|----------------|--|
| Composition | Vegetable oil and biodegradable surfactants. |
| Viscosity | 100-200 cps |
| Flash point | N/A |
| S.G. at 20°C | 1.0 |
| Coverage | 25-45m ² /litre |
| Freezing Point | 0°C |
| Colour | Off-white |
| Storage | 12 Months in frost free environment. |

Approved by WRAS for use with potable/wholesome water.
 Tested in accordance with BS6920:2000.

Note: Coverage will depend on surface porosity and texture.

Application Instructions

An even thin film of Biolease Standard should be applied by either low pressure spray, brush or an absorbent applicator. Applications should be performed a minimum of 1 hour prior to concrete installation, allowing the evaporation of the water phase, leaving a clear oily film. Over application should always be avoided, particularly on steel moulds as this can potentially pool, trapping the water phase and accelerate rust formation.

Consideration should be given to re-application if the coated formwork if stored for more than 14 days in an exposed environment. On vertical forms excess material accumulating at the bottom of the form should be removed. On untreated timber surfaces additional coats may be required.

Do not use below 5°C.

Storage

Biolease Standard should be stored at normal temperature, out of reach of children and away from foodstuffs. Shelf life of 12 months when stored in unopened containers. Roll or agitate container prior to use and especially important after long storage periods. Protect from frost.

Health & Environmental Considerations

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the very latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.

Packaging

Biolease Standard is available in 25 litre and 210 litre drums and in 1000 litre bulk tanks.



Technical Note

Biolease Standard, when used in accordance with the stated recommendations, does not cause staining. Concrete “staining” can be caused by a number of factors on which our technical department can advise.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.

