

## Uniseal Primer P3

### Porous Surface Primer

#### Description

Uniseal Primer P3 is a homogeneous solution of Bitumen in hydrocarbon solvents. It is used as a quick drying primer for use before the installation of bituminous materials such as Bituseal on porous substrates such as concrete.

#### Technical Information

Colour	Black
Specific Gravity	0.95
Flash Point	25°C
Non-volatile Content	<80%

#### Application Instructions

All surfaces should be dry and free from dust. Uniseal Primer P3 can be applied by brush or spray at an approximate theoretical spread rate of 7-12m<sup>2</sup> per litre dependant on the surface to be treated.

#### Packaging

Uniseal Primer P3 is supplied in 5 litre units.

#### Storage

Under good storage conditions and with the containers in an unopened condition, Uniseal Primer P3 may be stored indefinitely. Once the container has been opened, the product should be used within 6-8 weeks.

#### Health & Safety

Product Safety Data Sheets (SDS) are available from Nufins. SDS sheets are provided to help customers satisfy their safe handling, use and disposal needs as well as assist with any conformance requirements made locally by health and safety regulations.

SDS are continually updated to provide the latest information to our customers. We therefore recommend contacting our head office to obtain the most recent and accurate SDS before handling and using any product.

#### Technical support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors. Technical contacts are available to provide further information and arrange demonstrations.

