

# FORMSTRIKE MRO

## Concrete Release Agent

### Description

A versatile neat oil with surfactant which is designed to give optimum release and surface finish for a wide range of formwork materials. Complies with the British Cement Association, Category 2.

### Advantages

- Produces a uniform stain free concrete surface.
- Effects a positive release hence reducing cleaning time.
- Protects both metal and timber forms.
- Economical in use and easily applied.

### Technical Information

Appearance:	Low viscosity brown liquid
S.G. at 20°C:	0.84
Viscosity at 20°C:	13cp
Saponification value:	3.0
Freezing Point:	-25°C
Coverage m <sup>2</sup> /litre:	15-30

### Application Instructions

1. The form surface should be clean prior to application of the mould oil.
2. A thin even film should be applied preferably by spray, though brush or rollers may be used. Excess material should not be allowed to collect in the bottom of the moulds.
3. New unsealed timber requires a double application prior to the first cast.

### Packaging

Formstrike MRO is available in 25 litre and 210 litre drums and in 1000 litre bulk tanks.

### Storage

Mould Oils should be stored at normal temperature, out of the reach of children and away from foodstuffs.

### Health & Safety

Gloves and goggles should be worn when using this product. Accidental splashes on skin should be removed by washing with soap and water. Contact with eyes should be avoided and accidental contamination should be washed out and medical attention sought. If swallowed, do not induce vomiting and seek medical aid.

Ensure adequate ventilation and do not use near naked flames or smoke during use as this product is flammable.

### Technical Note

Formstrike MRO, when used in accordance with the manufacturers recommendations, does not cause staining. Concrete 'staining' can be caused by a number of factors on which our Technical Department can advise.

### Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors.

Technical representatives are available throughout the UK to provide further information and arrange demonstrations.



Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA, United Kingdom.

TEL: +44 (0) 191 416 8360 FAX: +44 (0) 191 415 5966 W: [www.nufins.com](http://www.nufins.com) E: [info@usluk.com](mailto:info@usluk.com)

The information and/or specifications contained herein or in our literature or given by Nufins, its employees, distributors, agents or representatives with regard to its product or their use or application are given in good faith, but no liability is accepted for any loss or damage (including direct or consequential loss or loss of profits) from the use of products because Nufins has no control over how its products are used and applied.