

NUTAPE & NUFOAM

Formwork Tapes

Nutape

A PVC waterproof matt tape available in two widths specially developed for use on all types of formwork to effectively seal against grout loss. Also suitable for many other site applications.

Advantages & Applications

- Easy to fix with maximum adhesion even on to slightly oily formwork surfaces.
- High resistance to oil, water and abrasion when in place.
- Eliminates remedial work on finished concrete surfaces.
- Ideal for soffit formwork and with PVC and polystyrene void formers.
- Ideal for use as damp proof membrane jointing tape.

Specification

Material:	PVC
Thickness:	0.17 mm
Length:	33 metres
Breaking Strength:	2.4 N/mm width

Packaging

Nutape 50mm:	18 rolls per carton
Nutape 75mm:	12 rolls per carton

Application Instructions

Ensure surfaces are reasonably dry and that all excess oil is removed.
Uncoil Nutape and apply to formwork joint. Do not apply under tension as this will effect a creepback of the film.

Storage

Nutape should be stored at normal temperatures and not allowed to freeze as this will lead to embrittlement of the film.

Limitations

When used on absorbent surfaces there could be a variation in concrete colour due to a local change of water cement ratio.

Nufoam

An adhesive foam strip designed to seal inaccessible joints to prevent grout loss.

Advantages & Applications

- Standard dimensions are suitable for the majority of formwork joints.
- Ideal for all inaccessible joints, e.g. column boxes and kickers.
- Incorporates a silicone backing for easy removal and rapid fixing.
- Will adhere on to slightly oily and damp formwork surfaces.
- Available in tropical grade.

Specification

Material:	Polyester, closed cell foam
Thickness:	6 mm
Width:	12 mm
Length of Roll:	12 metres

Packaging

Nufoam is supplied in cartons each containing 40 No. rolls.

Application Instructions

Ensure surfaces are reasonably dry and that any excess oil is removed.
Remove the silicone backing paper and place firmly into place.
Do not apply under tension.

Storage

Nufoam requires no special storage requirements but should not be subjected to excessive heat.

Limitations

Nufoam can only be used on thin joints. Wider foam tapes are available upon request.



Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA, United Kingdom.
TEL: +44 (0) 191 416 8360 FAX: +44 (0) 191 415 5966 W: www.nufins.com E: info@usluk.com

The information and/or specifications contained herein or in our literature or given by Nufins, its employees, distributors, agents or representatives with regard to its product or their use or application are given in good faith, but no liability is accepted for any loss or damage (including direct or consequential loss or loss of profits) from the use of products because Nufins has no control over how its products are used and applied.