

NULEASE VARNISH W.B.

Waterbased Formwork Coating

Description

A water based acrylic urethane clear sealer designed for applications onto wood and concrete formwork. This environmentally friendly product is characterised by its rapid drying, hard wearing, non-yellowing properties which gives maximum protection to timber formwork and moulds and helps ensure reproduction of high quality concrete finishes.

Available in Gloss and Matt forms.

Advantages

- Non-flammable, low odour formulation.
- Economical in use and equipment may be cleaned with water.
- Fine particle size ensures excellent penetration.
- Easily applied by brush or roller.

Technical Information

Drying Time:	40-45 mins @ 20°C
S.G.:	1.04
Coverage:	6-8 M ² per litre depending on surface profile and porosity.

Surface Preparation

All surfaces should be clean and free of all contaminants and should not have been previously treated with paints or oils.

Application Instructions

Nulease Varnish W.B. should be applied at the correct coverage rate using a brush, applicator or roller, thinning should not be necessary. Two coats are normally applied but on very porous surfaces or where a high build is required a third coat may be applied. Subsequent coats may be applied as soon as the previous coat is dry. All equipment should be cleaned immediately after use with clean water. Formwork should be allowed to dry for at least 48 hours prior to the application of a release agent and the placing of concrete.

Packaging

Nulease Varnish W.B. is available in 5 and 25 litre polythene bottles.

Health & Safety

Nulease Varnish W. B. is non-flammable and is considered non-hazardous. However normal precautions when handling chemicals must be observed including good skin care and the wearing of goggles. Splashes should be washed from the skin with soap and water before it dries.

Storage

Material should be stored at room temperature, protected from frost and kept out of the reach of children. Shelf life is limited to 12 months.

Limitations

Do not use on concrete which is to be submerged in water. Do not apply below 5°C or in damp or wet conditions or when rain is expected.

Technical Support

Through our technical department and laboratories we can offer a comprehensive service to specifiers and contractors.

Technical representatives are available throughout the UK to provide further information and arrange demonstrations.



Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA, United Kingdom.
TEL: +44 (0) 191 416 8360 FAX: +44 (0) 191 415 5966 W: www.nufins.com E: info@usluk.com

The information and/or specifications contained herein or in our literature or given by Nufins, its employees, distributors, agents or representatives with regard to its product or their use or application are given in good faith, but no liability is accepted for any loss or damage (including direct or consequential loss or loss of profits) from the use of products because Nufins has no control over how its products are used and applied.